

Environmental Product Declaration

Verified data according to EN15804+A2

This declaration is for:

BBI.007.U

Functional unit: **Piece**

Date of issue: **20-07-2026**

Expiry date: **13-2-2029**

Scope of LCA: **Cradle-to-Gate
including end-of-life**



LCA modules EN15804+A2:

A1	A2	A3	A4-5	B1-7	C1	C2	C3	C4	D
X	X	X	ND	ND	X	X	X	X	X

X = Modules assessed; ND = Not Declared

Scope of the declaration:

This is a self-declared EPD provided by **BOERplay B.V. – The Netherlands**. All the data in this EPD is based on a LCA-background dossier in accordance to the following standards and requirements of: **ISO 14040, ISO 14044, ISO 14025, EN15804+A2: 2019 and NMD Bepalingsmethode version 1.1 (March 2022)**. All the used data, methods, calculations, allocations and cut-offs with are used to calculate GWP total and the MKI score can be found in this dossier and are **verified by recognised LCA experts**. It is verified according to the MRPI and NMD verification protocol. Verification was performed in February 2024.

Global warming potential (GWP total)		Milieukostenindicator (MKI)*	
	737 kg CO ₂ /eq	€	€ 110,-

NOTE: EPDs of similar products may not be comparable if they do not comply with EN15804+A2:2019.

None of the substances contained in the product are listed in the “Candidate List of Substances of Very High Concern for authorisation”, or they do not exceed the threshold with the European Chemicals Agency.

DEMONSTRATION OF VERIFICATION

CEN standard EN15804 serves as the core PCR**

Independent verification of the calculation method leading to the values stated in this document according to MRPI and NMD verification protocol.

Third party verifier:

SGS Intron B.V.

verified by: U. Hofstra

*Environmental Cost Indicator (Dutch single score in EUR)

**Product Category Rules

TOE.BBI.007.U						
Material	Weight (kg)	Impact category	GWP (kg CO2 eq.)	MKI (€)	Recycled material (kg)	Recyclable material (kg)
Aluminum K-alloy	0,2	OME_ALU_CAST	1,3	0,19	0,0	0,0
Aluminum Post Coated	42,6	OME_ALU_POST	185,9	26,01	42,6	42,6
Hardwood Post	44,3	OHO_SHO_HHT	19,5	2,22	0,0	0,0
HDPE	51,3	OPE_HDPE_BC	229,9	21,55	41,1	51,3
HDPE	4,8	OPE_HDPE_WC	23,6	2,00	0,0	4,8
PA6 GFR	0,2	KST_PA_INJECTION	2,2	0,16	0,0	0,2
PA6	0,2	KST_PA_INJECTION	1,6	0,12	0,0	0,2
PA6.6	0,5	KST_PA_INJECTION	5,3	0,40	0,0	0,5
ReBo	46,6	ORE_REBO_NL	176,7	16,78	46,6	46,6
Rope Hercules 16mm	0,2	ONT_SNT_ROPE	2,3	0,07	0,0	0,0
Sendzimir Plate	2,7	SME_STEEL_NL	5,7	3,19	0,0	2,7
Stainless Steel 304	4,2	BSR_RVS	12,2	8,27	0,0	4,2
Stainless Steel 304	32,0	SME_RVS_PL	57,2	27,81	0,0	32,0
Stainless Steel 316	0,1	SME_RVS_PL	0,2	0,10	0,0	0,1
Steel Galvanized	0,3	SME_STEEL_COAT_PL	0,8	0,36	0,0	0,3
Overhead (1 pcs)	-	Overhead	13,0	0,94	-	-
--- Total ---	230kg	-	737 kg CO2 eq.	€ 110,16	130 kg (56,6 %)	185 kg (80,6 %)