

Environmental Product Declaration

Verified data according to EN15804+A2

This declaration is for:

BBP.214.5BR

Functional unit: **Piece**

Date of issue: **20-07-2026**

Expiry date: **13-2-2029**

Scope of LCA: **Cradle-to-Gate
including end-of-life**



LCA modules EN15804+A2:

A1	A2	A3	A4-5	B1-7	C1	C2	C3	C4	D
X	X	X	ND	ND	X	X	X	X	X

X = Modules assessed; ND = Not Declared

Scope of the declaration:

This is a self-declared EPD provided by **BOERplay B.V. – The Netherlands**. All the data in this EPD is based on a LCA-background dossier in accordance to the following standards and requirements of: **ISO 14040, ISO 14044, ISO 14025, EN15804+A2: 2019 and NMD Bepalingsmethode version 1.1 (March 2022)**. All the used data, methods, calculations, allocations and cut-offs with are used to calculate GWP total and the MKI score can be found in this dossier and are **verified by recognised LCA experts**. It is verified according to the MRPI and NMD verification protocol. Verification was performed in February 2024.

Global warming potential (GWP total)		Milieukostenindicator (MKI)*	
	2377 kg CO ₂ /eq	€	€ 487,-

NOTE: EPDs of similar products may not be comparable if they do not comply with EN15804+A2:2019.

None of the substances contained in the product are listed in the “Candidate List of Substances of Very High Concern for authorisation”, or they do not exceed the threshold with the European Chemicals Agency.

DEMONSTRATION OF VERIFICATION

CEN standard EN15804 serves as the core PCR**

Independent verification of the calculation method leading to the values stated in this document according to MRPI and NMD verification protocol.

Third party verifier:

SGS Intron B.V.

verified by: U. Hofstra

*Environmental Cost Indicator (Dutch single score in EUR)

**Product Category Rules

TOE.BBP.214.5BR						
Material	Weight (kg)	Impact category	GWP (kg CO2 eq.)	MKI (€)	Recycled material (kg)	Recyclable material (kg)
Aluminum K-alloy	1,4	OME_ALU_CAST	10,3	1,55	0,0	0,0
Aluminum Post Coated	77,3	OME_ALU_POST	337,0	47,16	77,3	77,3
Aluminum	55,9	SME_ALU_PL	373,5	51,44	0,0	55,9
Concrete	463,2	OBT_SNELBETON	74,1	9,26	0,0	0,0
HDPE	162,7	OPE_HDPE_BC	728,7	68,32	130,1	162,7
LDPE Sheet	24,0	KST_LDPE	103,5	9,85	23,3	24,0
PA6 GFR	0,3	KST_PA_INJECTION	2,9	0,22	0,0	0,3
PA6	1,2	KST_PA_INJECTION	12,7	0,95	0,0	1,2
PA6.6	1,1	KST_PA_INJECTION	11,5	0,86	0,0	1,1
Polyester	4,5	KST_POL_PL	29,0	3,88	0,0	0,0
ReBo	32,3	ORE_REBO_NL	122,3	11,62	32,3	32,3
Rope Hercules 16mm	7,4	ONT_SNT_ROPE	86,7	2,50	0,0	0,0
Sendzimir Plate	7,3	SME_STEEL_NL	15,1	8,49	0,0	7,3
Stainless Steel 304	7,9	BSR_RVS	22,8	15,49	0,0	7,9
Stainless Steel 304	39,0	SME_RVS_PL	69,7	33,89	0,0	39,0
Stainless Steel 304	69,4	SME_RVS_SLIDE_NL	215,1	156,78	0,0	69,4
Stainless Steel 316	0,4	SME_RVS_PL	0,8	0,38	0,0	0,4
Steel Galvanized	0,2	BSV_GALV	0,6	0,25	0,0	0,2
Steel Galvanized	50,6	SME_STEEL_COAT_PL	147,3	63,26	0,0	50,6
Overhead (1 pcs)	-	Overhead	13,0	0,94	-	-
--- Total ---	543kg	-	2377 kg CO2 eq.	€ 487,09	263 kg (48,5 %)	529 kg (97,6 %)
Total weight, incl Concrete	1006 kg	-	-	-	-	-